


## EC DECLARATION OF CONFORMITY (DEKLARACIJA O USAGLAŠENOSTI)

No/Br. EC10.01.01/16

<b>We/Mi</b>	<b>Metalka Majur, Vihorska 9, 35000 Jagodina, Srbija</b>
<b>declare under our sole responsibility that the product</b> / <i>izjavljujemo pod sopstvenom odgovornošću da je proizvod</i>	<b>Residual current device</b> <i>Prekidači diferencijalne struje</i>
<b>production program</b> / <i>proizvodnog programa</i>	<b>(reference the attached of catalog number, name and other characteristics</b> / <i>brojevi artikala, nazivi, tipovi i druge karakteristike su date u prilogu</i> )
<b>standards applied</b> / <i>u skladu sa sledećim standardima i normativnim dokumentima</i>	<b>EN 61008: 2012</b> <b>SRPS EN 61008: 2014</b>
<b>Directives</b> / <i>Pravilnici</i>	<b>2006/95/EC Low Voltage Directive</b> <b>2004/108/EC Electromagnetic Compatibility Directive</b> <i>Pravilnik o električnoj opremi namenjenoj za upotrebu u okviru određenih granica napona („Sl.glasnik RS“, br. 13/2010)</i> <i>Pravilnika o elektromagnetnoj kompatibilnosti (Sl. glasnik RS broj 13/10)</i>
<b>Certificates</b> / <i>Potvrde o usaglašenosti</i>	<b>FI 23617</b>
<b>Notified body</b> / <i>Imenovano telo</i>	<b>Fimko, Helsinki</b>
<b>CE marking</b> / <i>CE označavanje</i>	<b>12</b>
<b>Place and date of issue</b> / <i>Mesto i datum izdavanja deklaracije</i>	<b>Jagodina, 06.05.2016</b>
<b>CE</b>	<b>Signature:</b>  Name: Dona Stevanović Position: Quality control manager

**Attached / Prilog:**

Art No	Name / Naziv	Characteristics / Karakteristike
31.01.001	Socket with residual current device <i>Priključnica sa integrisanom strujnom zaštitnom sklopkom</i>	Rated voltage: 230VAC (45-60)Hz, Rated electric current: 16A Rated differential electric current: 30mA Diameter of conductor: (1,5-2,5)mm <sup>2</sup> Temperature range: (-25...+40)°C  <i>Naznačeni napon: 230VAC (45-60)Hz, Naznačena struja: 16A Naznačena diferencijalna struja: 30mA Presek provodnika: (1,5-2,5)mm<sup>2</sup> Temperatura okoline: (-25...+40)°C</i>
31.01.002	Socket with residual current device (blind type) <i>Samostalna strujna zaštitna sklopka</i>	Rated voltage: 230VAC (45-60)Hz, Rated electric current: 16A Rated differential electric current: 30mA Diameter of conductor: (1,5-2,5)mm <sup>2</sup> Temperature range: (-25...+40)°C  <i>Naznačeni napon: 230VAC (45-60)Hz, Naznačena struja: 16A Naznačena diferencijalna struja: 30mA Presek provodnika: (1,5-2,5)mm<sup>2</sup> Temperatura okoline: (-25...+40)°C</i>